


IN-FINITY 70 SUSPENSION UP & DOWN 3000K GENERAL LIGHTING

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 35,9W/m 3000K CRI 80 1536 lm/m UP - 2877 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Up & Down 3000K General Lighting
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	103°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

- N70U113G30B 1125mm - 3821lm White
- N70U113G02B 1125mm - 3821lm Anodized Grey
- N70U113G14B 1125mm - 3821lm Black
- N70U143G30B 1405mm - 4776lm White
- N70U143G02B 1405mm - 4776lm Anodized Grey
- N70U143G14B 1405mm - 4776lm Black
- N70U193G30B 1970mm - 6687lm White
- N70U193G02B 1970mm - 6687lm Anodized Grey
- N70U193G14B 1970mm - 6687lm Black
- N70U303G30B 3095mm - 10507lm White
- N70U303G02B 3095mm - 10507lm Anodized Grey
- N70U303G14B 3095mm - 10507lm Black
- N70UFC3G30B Flat Corner - 3821lm White
- N70UFC3G02B Flat Corner - 3821lm Anodized Grey
- N70UFC3G14B Flat Corner - 3821lm Black
- N70UEM3G30B Emergency - 4776lm White
- N70UEM3G02B Emergency - 4776lm Anodized Grey
- N70UEM3G14B Emergency - 4776lm Black
- N70U083G30B 845mm - 2866lm White
- N70U083G02B 845mm - 2866lm Anodized Grey
- N70U083G14B 845mm - 2866lm Black
- N70U163G30B 1690mm - 5731lm White
- N70U163G02B 1690mm - 5731lm Anodized Grey
- N70U163G14B 1690mm - 5731lm Black
- N70U253G30B 2530mm - 8597lm White
- N70U253G02B 2530mm - 8597lm Anodized Grey
- N70U253G14B 2530mm - 8597lm Black

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 70 Suspension Up & Down 3000K General Lighting . Accessories

Structural



- 08.9057.40
- 08.9057.02
- 08.9057.NS
- 08.9057.06

Metal cover. Suspension Up & Down. 70 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 70 Suspension Up & Down 3000K General Lighting designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N70U113G30B 1125mm - 3821lm White
- N70U113G02B 1125mm - 3821lm Anodized Grey
- N70U113G14B 1125mm - 3821lm Black
- N70U143G30B 1405mm - 4776lm White
- N70U143G02B 1405mm - 4776lm Anodized Grey
- N70U143G14B 1405mm - 4776lm Black
- N70U193G30B 1970mm - 6687lm White
- N70U193G02B 1970mm - 6687lm Anodized Grey
- N70U193G14B 1970mm - 6687lm Black
- N70U303G30B 3095mm - 10507lm White
- N70U303G02B 3095mm - 10507lm Anodized Grey
- N70U303G14B 3095mm - 10507lm Black
- N70UFC3G30B Flat Corner - 3821lm White
- N70UFC3G02B Flat Corner - 3821lm Anodized Grey
- N70UFC3G14B Flat Corner - 3821lm Black
- N70UEM3G30B Emergency - 4776lm White
- N70UEM3G02B Emergency - 4776lm Anodized Grey
- N70UEM3G14B Emergency - 4776lm Black
- N70U083G30B 845mm - 2866lm White
- N70U083G02B 845mm - 2866lm Anodized Grey
- N70U083G14B 845mm - 2866lm Black
- N70U163G30B 1690mm - 5731lm White
- N70U163G02B 1690mm - 5731lm Anodized Grey
- N70U163G14B 1690mm - 5731lm Black
- N70U253G30B 2530mm - 8597lm White
- N70U253G02B 2530mm - 8597lm Anodized Grey
- N70U253G14B 2530mm - 8597lm Black



In-Finity 70 Suspension Up & Down 3000K General Lighting . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 70 Suspension Up & Down 3000K General Lighting . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 70 Suspension Up & Down 3000K General Lighting designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N70U113G30B 1125mm - 3821lm White
- N70U113G02B 1125mm - 3821lm Anodized Grey
- N70U113G14B 1125mm - 3821lm Black
- N70U143G30B 1405mm - 4776lm White
- N70U143G02B 1405mm - 4776lm Anodized Grey
- N70U143G14B 1405mm - 4776lm Black
- N70U193G30B 1970mm - 6687lm White
- N70U193G02B 1970mm - 6687lm Anodized Grey
- N70U193G14B 1970mm - 6687lm Black
- N70U303G30B 3095mm - 10507lm White
- N70U303G02B 3095mm - 10507lm Anodized Grey
- N70U303G14B 3095mm - 10507lm Black
- N70UFC3G30B Flat Corner - 3821lm White
- N70UFC3G02B Flat Corner - 3821lm Anodized Grey
- N70UFC3G14B Flat Corner - 3821lm Black
- N70UEM3G30B Emergency - 4776lm White
- N70UEM3G02B Emergency - 4776lm Anodized Grey
- N70UEM3G14B Emergency - 4776lm Black
- N70U083G30B 845mm - 2866lm White
- N70U083G02B 845mm - 2866lm Anodized Grey
- N70U083G14B 845mm - 2866lm Black
- N70U163G30B 1690mm - 5731lm White
- N70U163G02B 1690mm - 5731lm Anodized Grey
- N70U163G14B 1690mm - 5731lm Black
- N70U253G30B 2530mm - 8597lm White
- N70U253G02B 2530mm - 8597lm Anodized Grey
- N70U253G14B 2530mm - 8597lm Black

