


## IN-FINITY 70 SUSPENSION UP & DOWN 4000K GENERAL LIGHTING

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant up & down
<b>Lamps description</b>	Top LED 35,9W/m 4000K CRI 80 1680 lm/m UP - 3091 lm/m DOWN
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



**In-Finity 70 Suspension Up & Down 4000K General Lighting**  
designed by FLOS Architectural

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Direct - Indirect
<b>Beam angle</b>	103°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

- N70U114G30B 1125mm - 4137lm White
- N70U114G02B 1125mm - 4137lm Anodized Grey
- N70U114G14B 1125mm - 4137lm Black
- N70U144G30B 1405mm - 5171lm White
- N70U144G02B 1405mm - 5171lm Anodized Grey
- N70U144G14B 1405mm - 5171lm Black
- N70U194G30B 1970mm - 7240lm White
- N70U194G02B 1970mm - 7240lm Anodized Grey
- N70U194G14B 1970mm - 7240lm Black
- N70U304G30B 3095mm - 11377lm White
- N70U304G02B 3095mm - 11377lm Anodized Grey
- N70U304G14B 3095mm - 11377lm Black
- N70UFC4G30B Flat Corner - 4137lm White
- N70UFC4G02B Flat Corner - 4137lm Anodized Grey
- N70UFC4G14B Flat Corner - 4137lm Black
- N70UEM4G30B Emergency - 5171lm White
- N70UEM4G02B Emergency - 5171lm Anodized Grey
- N70UEM4G14B Emergency - 5171lm Black
- N70U084G30B 845mm - 3103lm White
- N70U084G02B 845mm - 3103lm Anodized Grey
- N70U084G14B 845mm - 3103lm Black
- N70U164G30B 1690mm - 6205lm White
- N70U164G02B 1690mm - 6205lm Anodized Grey
- N70U164G14B 1690mm - 6205lm Black
- N70U254G30B 2530mm - 9308lm White
- N70U254G02B 2530mm - 9308lm Anodized Grey
- N70U254G14B 2530mm - 9308lm Black

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



## In-Finity 70 Suspension Up & Down 4000K General Lighting . Accessories

### Structural



- 08.9057.40
- 08.9057.02
- 08.9057.NS
- 08.9057.06

#### Metal cover. Suspension Up & Down. 70 mm

Metal cover for the different profiles. 2 unit kit.


### Mounting



- 08.0030

#### Suspension kit


One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.



### In-Finity 70 Suspension Up & Down 4000K General Lighting designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N70U114G30B 1125mm - 4137lm White
- N70U114G02B 1125mm - 4137lm Anodized Grey
- N70U114G14B 1125mm - 4137lm Black
- N70U144G30B 1405mm - 5171lm White
- N70U144G02B 1405mm - 5171lm Anodized Grey
- N70U144G14B 1405mm - 5171lm Black
- N70U194G30B 1970mm - 7240lm White
- N70U194G02B 1970mm - 7240lm Anodized Grey
- N70U194G14B 1970mm - 7240lm Black
- N70U304G30B 3095mm - 11377lm White
- N70U304G02B 3095mm - 11377lm Anodized Grey
- N70U304G14B 3095mm - 11377lm Black
- N70UFC4G30B Flat Corner - 4137lm White
- N70UFC4G02B Flat Corner - 4137lm Anodized Grey
- N70UFC4G14B Flat Corner - 4137lm Black
- N70UEM4G30B Emergency - 5171lm White
- N70UEM4G02B Emergency - 5171lm Anodized Grey
- N70UEM4G14B Emergency - 5171lm Black
- N70U084G30B 845mm - 3103lm White
- N70U084G02B 845mm - 3103lm Anodized Grey
- N70U084G14B 845mm - 3103lm Black
- N70U164G30B 1690mm - 6205lm White
- N70U164G02B 1690mm - 6205lm Anodized Grey
- N70U164G14B 1690mm - 6205lm Black
- N70U254G30B 2530mm - 9308lm White
- N70U254G02B 2530mm - 9308lm Anodized Grey
- N70U254G14B 2530mm - 9308lm Black



## In-Finity 70 Suspension Up & Down 4000K General Lighting . Accessories

### Electrical



08.0031.00

#### Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

## In-Finity 70 Suspension Up & Down 4000K General Lighting . Lamps



#### Top LED

#### Lamp category:


LED

#### Socket:

Special base

#### Lamp type:

Top LED



### In-Finity 70 Suspension Up & Down 4000K General Lighting designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N70U114G30B 1125mm - 4137lm White
- N70U114G02B 1125mm - 4137lm Anodized Grey
- N70U114G14B 1125mm - 4137lm Black
- N70U144G30B 1405mm - 5171lm White
- N70U144G02B 1405mm - 5171lm Anodized Grey
- N70U144G14B 1405mm - 5171lm Black
- N70U194G30B 1970mm - 7240lm White
- N70U194G02B 1970mm - 7240lm Anodized Grey
- N70U194G14B 1970mm - 7240lm Black
- N70U304G30B 3095mm - 11377lm White
- N70U304G02B 3095mm - 11377lm Anodized Grey
- N70U304G14B 3095mm - 11377lm Black
- N70UFC4G30B Flat Corner - 4137lm White
- N70UFC4G02B Flat Corner - 4137lm Anodized Grey
- N70UFC4G14B Flat Corner - 4137lm Black
- N70UEM4G30B Emergency - 5171lm White
- N70UEM4G02B Emergency - 5171lm Anodized Grey
- N70UEM4G14B Emergency - 5171lm Black
- N70U084G30B 845mm - 3103lm White
- N70U084G02B 845mm - 3103lm Anodized Grey
- N70U084G14B 845mm - 3103lm Black
- N70U164G30B 1690mm - 6205lm White
- N70U164G02B 1690mm - 6205lm Anodized Grey
- N70U164G14B 1690mm - 6205lm Black
- N70U254G30B 2530mm - 9308lm White
- N70U254G02B 2530mm - 9308lm Anodized Grey
- N70U254G14B 2530mm - 9308lm Black

