




## TECHNICAL DATA SHEET ART. S.6509 - BUL 18



TC-DEL 10W G24q-1 600lm  
 Rated luminaire luminous flux: 258lm  
 Rated input power: 15W  
 Luminaire efficacy: 17lm/W (LOR: 43%)  
 Electronic ballast 230÷240V 50/60Hz



CE IP 54

### PRODUCT TYPE

Wall mounted luminaire. IP rating IP 54

### MATERIAL CHARACTERISTICS

Aluminium die cast housing in EN AB-47100 (low copper content) with high resistance against corrosion. Stone wash surface treatment prior to painting process. A4 grade Stainless Steel screws with 2,5-3% molybdenum content which increases the resistance against corrosion. EPDM gaskets. Painting Process : 3 Step Process

1) Surface treatment with BONDERITE. A heavy metal free chemical surface treatment containing ceramic nano particles giving a cohesive, inorganic and highly dense protective coating. 2) PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. 3) POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1200h. Mechanical resistance IK 06

### LIGHTING PERFORMANCE

Sand blasted glass diffuser. Lamp fixed position. LOR 43%

### WIRING

Supply double cable entry. Isolation: CLASS I . Available colours: White (cod.01), Black (cod.09), Aluminium grey (cod.14). Weight: 1.4 Kg Glow Wire test: 960°C

**Lamp not included.**

**This luminaire is compatible with bulbs of the energy classes: B (Regulation UE 874/2012).**

### EMERGENCY VERSIONS

On request the fittings could be provided with electronic ballast which operate both on AC ( 50/60Hz ), both on DC ( 0Hz ) voltage.