



## UNO LUX

brushed aluminium, round, LED, 6W, 38°, 3000K, incl. driver

Article number	1000252
Feed-in capability	No
Lamp included	No
Tilt range	30 Degree
Rotation range	100 Degree
Height	9.5 cm
Diameter	8.5 cm
Net weight	0.58 kg
Gross weight	0.692 kg
Voltage	100-240V ~50/60Hz sec. 350mA
Protection class	I
Beam angle	38 Degree
Average lifespan	40000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	670 lm
Energy efficiency class	A++
Way of mounting	Surface mounted / Ceiling mounted
Colour	brushed aluminium
Form	round
Light distribution type 1	direct
Light distribution type 2	rotational symmetric
Material	Aluminium

#### Articles of this series

113931	TRILEDO ROUND CL ceiling light, LED, 3000K, round, white, 38°, 6.2W, incl. driver
113936	TRILEDO ROUND CL ceiling light, LED, 3000K, round, brushed aluminium, 38°, 8.2W, incl. driver
1000251	UNO LUX, matt white, round, LED, 6W, 38°, 3000K, incl. driver

The twisting and tilting ceiling light UNO LUX ROUND CL is made of aluminium and comes in housing colours of white, brushed aluminium and matt black. Thanks to its aluminium lamp head, the cone of light can be individually aligned. Fitted with an efficient COB LED with 6.2W and with the driver included, it can be connected directly to the 230V mains supply. This luminaire contains built-in LED lamps. EEL: A - A++.

#### Notes