



NUMINOS® MOVE DL L

Indoor LED recessed ceiling light black/chrome 4000K
40° rotating and pivoting

From hotels and offices to commercial or private rooms. From application to technology to design in detail: it's good that the modular downlights and spotlights can be configured exactly as required by the design or space in question. The more multifaceted your project is, the more you can benefit from the intelligent NUMINOS® lighting system. Thanks to the wide selection of modules, there is a suitable solution for every need. Combined with the suitable driver, the NUMINOS® lighting family, which can be freely configured and combined, offers over a thousand possibilities. Like the downlight, which can be swivelled through 30° and rotated through 355°. This features a selection of reflectors with half beam angles of 20°, 40° or 55°, enabling you to create strong lighting accents on walls in offices and for changing objects such as merchandise in shops. With the best workmanship and light quality. You can simply select the desired LED driver (on/off, phase dimming, DALI) for each total wattage via colour coding. This makes easy installation a matter of formality. When will you choose SLV's modular variety? - Here you can find the configurator: www.NUMINOS.SLV.com

TECHNICAL DATA

| | |
|-------------------------------------|---------------------------|
| Item no.: | 1003678 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 700 mA/V |
| Height | 9.5 cm |
| Diameter | 16.0 cm |
| Installation diameter | 14.5 cm |
| Installation depth | 10.5 cm |
| Net weight | 0.49 kg |
| Gross weight | 0.524 kg |
| IP Code | IP 20 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,20000000000000001 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 25.41 W |
| Lumen | 2350 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 40 ° |
| Color | black |
| CRI | >90 |
| UGR ≤ | 18 |

Accessories

| | |
|---------|---|
| 1004062 | LED driver , 21-29.5W 500/600/700mA |
| 1004065 | LED driver , 30W 700mA |
| 1004070 | LED driver , 1.5-40,6W 250/350/500/700mA |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1004797 | NUMINOS® L , diffuser Wabe |

| | |
|-----------------------------|---------|
| Binning | 3 |
| LXXBXX data | 80/50 |
| Service life | 50000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 37 |

Notes
