

3~ NUMINOS® PHASE S

3 phase system light black/black 4000K 60°

No two projects are the same. But many projects demand a coherent lighting and design concept. NUMINOS® is a perfectly coordinated lighting system that harmonises function, design and technology. For planners and doers, for every requirement and for maximum variety with minimum effort. From hotels and offices to commercial or private rooms. From application to technology to design in detail: the modular downlights and spotlights can be configured exactly as required by the design or spatial conditions in question. The more multifaceted your project is, the more you can benefit from the intelligent NUMINOS® lighting system. Thanks to the wide selection of modules, there is a suitable solution for every need. The NUMINOS® lighting family, which can be configured and combined, offers over a thousand possibilities. Like the 3-circuit track spotlight, with which you can adapt the lighting effect to suit the lighting context in question. With the best workmanship and light quality, which is infinitely variable thanks to the integrated LED driver (phase dimming). Easy installation and alignment within the track is just a matter of formality. When will you choose SLV's modular variety? Here you can find the configurator: www.NUMINOS.SLV.com

TECHNICAL DATA

Item no.:	1004092
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250 mA/V
Vertical tilting range	90 °
Horizontal rotation range	350 °
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.53 kg
Gross weight	0.567 kg
Safety class	I
Assembly details	Track Ceiling, Track Wall
Assembly details	Track Deliing, track Wall
Dimming technology	trailing edge
Dimming technology	trailing edge
Dimming technology Wattage	trailing edge 10.42 W
Dimming technology Wattage Lumen	trailing edge 10.42 W 1100 Im
Dimming technology Wattage Lumen Colour temperature	trailing edge 10.42 W 1100 Im 4000 Kelvin
Dimming technology Wattage Lumen Colour temperature Beam angle	trailing edge 10.42 W 1100 Im 4000 Kelvin 60 °
Dimming technology Wattage Lumen Colour temperature Beam angle Color	trailing edge 10.42 W 1100 Im 4000 Kelvin 60 ° black
Dimming technology Wattage Lumen Colour temperature Beam angle Color CRI	trailing edge 10.42 W 1100 Im 4000 Kelvin 60 ° black >90
Dimming technology Wattage Lumen Colour temperature Beam angle Color CRI UGR ≤	trailing edge 10.42 W 1100 Im 4000 Kelvin 60 ° black >90 19





Service life	50000 h
BIG WHITE Page	43

Notes			