




OCULUS CL

Indoor LED wall and ceiling mounted light white
DIM-TO-WARM 2000-3000K

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light (2000-3000K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



TECHNICAL DATA

Item no.:	1004667
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250 mA/V
Height	9.0 cm
Diameter	9.0 cm
Net weight	0.57 kg
Gross weight	0.61 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimming technology	trailing edge
Wattage	11 W
Lumen	36 - 780 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °
Color	white
CRI	>90
Binning	3
LXXBXX data	70/50
Service life	25000 h



Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
BIG WHITE Page	315

Notes
