



MILANDOS 8

white recessed ceiling light, 2700K 45°

Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. The long LED lifespan of 60,000 hours and the high colour reproduction index of over 90 are also convincing across the board. With its simple design, the square recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. With a UGR of 23, it conjures up a high-quality, glare-free light. The spotlight is also quick and easy to install. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.

TECHNICAL DATA

| Item no. | 1005425 |
|---------------------------|-------------|
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Wattage | 16 W |
| Ambient temperature | 30 °C |
| Lumen | 1280 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 45 ° |
| Color | white |
| CRI | 90 |
| UGR≤ | 23 |
| LXXBXX data | L80B50 |
| Service life | 60000 h |
| Risk Group | 1 |
| Length | 25.6 cm |
| Width | 5.6 cm |
| Height | 4.3 cm |
| Net weight | 0.4 kg |
| | |



Light Source

| 1078067 | A E |
|-------------|--|
| 1078460 | A E |
| Accessories | |
| 1002423 | LED driver MEDO 300 , dimmable DALI/1-10V |
| 1006202 | LED Driver . 20W 700mA |

| Gross weight | 0.428 kg |
|---------------------|----------|
| Shape of cut-out | square |
| Installation length | 25 cm |
| Installation width | 4.9 cm |
| Installation depth | 7 cm |
| | |