




DASAR FLAT 120 EL

stainless steel in-ground light, 7 W 3000 K

The DASAR FLAT 120 EL high-voltage recessed ground light can be walked on and impresses with its stainless steel screen and glass cover in a partial satin finish. Added to this is the high-quality housing made of 304 stainless steel. See the outdoor lights in action and let yourself be impressed by a stunning lighting experience.



TECHNICAL DATA

Item no.	1006106
IP Code	IP65/IP67
Impact resistance class	IK 08
Impact resistance	5 Joule
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0.5
Number of luminaires at LS B16A	112
Number of luminaires at LS C16A	200
Level of inrush current	10 A
Duration of inrush current	100 µs
Lumen	490 lm
Colour temperature	3000 Kelvin
Color	stainless steel
CRI	80
Service life	30000 h
Risk Group	1
Depth	8 cm

Light Source

916531	
--------	---

Diameter	12 cm
Net weight	0.708 kg
Gross weight	0.793 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	10.6 cm
BIG WHITE Page	969