


## GRIP! S

**48V spot, deep & recessed track, cylindrical, 2700K, 9.8 Watt, DALI, 29°, white / black**

GRIP! combines modern design and high quality lighting technology - now available in a recessed version for the SLV 48V track system. The GRIP! S 48V DALI spots impress with precise light control, minimalist design and aesthetic colour variants. Compatible with both the 48V mounting track and the 48V recessed track, they are ideal for discreet integration into architecturally sophisticated ceiling designs. All GRIP! Spots are supplied with a honey-comb grid as standard - for glare-free light and optimum visual comfort. Available in three light colours: 2,700 K, 3,000 K or dim-to-warm 2,000-3,000 K and in the housing colours bronze, gold, black and white, the spots offer a wide range of design options. For even more individuality, they can be combined with separately available decorative rings in contemporary colours. Integrated DALI control ensures professional lighting control in any environment. GRIP! - The decorative 48V spot for sophisticated lighting with style.



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1009024     |
| Number of different light outlets | 1           |
| IP Code                           | IP20        |
| Impact resistance class           | IK 02       |
| Impact resistance                 | 0.2 Joule   |
| Assembly details                  | Ceiling     |
| Dimmable                          | Yes         |
| Dimming technology                | DALI        |
| Primary nominal voltage           | 48DC        |
| Secondary power / voltage         | 250 mA      |
| Safety class                      | III         |
| Wattage                           | 9.8 W       |
| Minimum ambient temperature       | 0 °C        |
| Maximum ambient temperature       | 35 °C       |
| Lumen                             | 590 lm      |
| Colour temperature                | 2700 Kelvin |
| Beam angle                        | 29 °        |
| Color                             | white/black |
| CRI                               | 90          |
| UGR ≤                             | 25          |
| Service life                      | 50000 h     |
| Risk Group                        | 1           |

## Light Source

|         |   |
|---------|---|
| 2093820 |  |
|---------|---|

## Accessories

|         |                                   |
|---------|-----------------------------------|
| 1008489 | GRIP! S , decorative ring, black  |
| 1008488 | GRIP! S , decorative ring, white  |
| 1008490 | GRIP! S , decorative ring, nickel |
| 1008491 | GRIP! S , decorative ring, gold   |

|              |          |
|--------------|----------|
| Length       | 18 cm    |
| Width        | 3 cm     |
| Height       | 6.7 cm   |
| Net weight   | 0.12 kg  |
| Gross weight | 0.162 kg |