




DOWNLIGHT C

150 8/14/20W 930 IP54

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the DOWNLIGHT C recessed luminaires, which are ideal for general lighting in commercial environments. They are available in two different cut-outs (150 mm and 200 mm) and offer a colour temperature of 3000K or 4000K. You can also choose from an on/off version with switchable system output and a DALI-controllable version. With their eligible energy efficiency and a lumen output of up to 3,100 lm, you can experience sustainable lighting in commercial spaces.



TECHNICAL DATA

Item no.	1008621
IP Code	IP54
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Number of through-wires	36
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	200/350/500 mA
Safety class	II
Wattage	8 W
Ambient temperature	70 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	36
Number of luminaires at LS C16A	60
Level of inrush current	16 A
Duration of inrush current	100 µs
Lumen	950/1550/2250 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
UGR ≤	22

Service life	70000 h
Height	8.6 cm
Diameter	17.6 cm
Net weight	0.5 kg
Gross weight	0.6 kg
Shape of cut-out	round
Installation depth	9 cm
Installation diameter	15.5 cm