




round, aluminium anodized, max. 50W







| Article number | 111308 |
|------------------------------|---|
| Type of lamp | Conventional lamp |
| Lamp | MR16 12V max. 50W |
| Lampholder / Socket | G5,3 |
| Number of light sources | 1 |
| Lamp included | No |
| Installation diameter | 6.5 cm |
| Installation depth | 14 cm |
| Diameter | 7 cm |
| Net weight | 0.119 kg |
| Gross weight | 0.188 kg |
| Voltage | 12 Volt |
| Max. wattage | 50 Watt |
| Protection class | III |
| Material | aluminium |
| Colour | aluminium |
| Way of mounting | recessed ceiling mounting |
| Remark 1 | Not suitable for the use of cool-beam lamps |
| Remark 2 | Energy labels in your language are available in the Service Area sub point Download |
| Suitable for lamps from EEC | С |
| Suitable for lamps up to EEC | A+ |
| Light distribution type 1 | direct |
| Light distribution | rotationally symmetric |

The low-voltage downlight SLIM MR16 is made from anodized aluminium. Designed for the use of low-voltage halogen lamps, a suitable transformer providing 12V alternating current is required for operation. This luminaire is compatible with bulbs of the energy classes: C - A+

rotationally symmetric

type 3