


MR16 SP downlight

round, white, MR16, max. 50W



| | |
|------------------------------|---|
| Article number | 112091 |
| Type of lamp | Conventional lamp |
| Lamp | MR16 12V max. 50W |
| Lampholder / Socket | G5,3 |
| Number of light sources | 1 |
| Lamp included | No |
| Installation diameter | 7.6 cm |
| Installation depth | 9.5 cm |
| Tilt range | 30 Degree |
| Diameter | 8.2 cm |
| Net weight | 0.109 kg |
| Gross weight | 0.24 kg |
| Voltage | 12 Volt |
| Max. wattage | 50 Watt |
| Protection class | III |
| Material | aluminium |
| Colour | white |
| Way of mounting | recessed ceiling mounting |
| Remark 1 | Not suitable for the use of cool-beam lamps |
| Remark 2 | Energy labels in your language are available in the Service Area sub point Download |
| Suitable for lamps from EEC | C |
| Suitable for lamps up to EEC | A+ |
| Light distribution type 1 | direct |
| Light distribution type 3 | rotationally symmetric |



The low voltage MR11 SP downlight from aluminum is available in the white, silvergrey, black, chrome and satin chrome finish. The recessed ring is rotatable and designed for one low-voltage halogen lamp with MR16 Socket. To operate the downlight a suitable transformer providing 12V alternating voltage is needed. This luminaire is compatible with bulbs of the energy classes: C - A+