



## AIXLIGHT PRO T5 FRAMELESS

square, black, Energy Saver, max. 2x39W

Article number	115250
Type of lamp	Conventional lamp
Lamp	T5 fluorescent bulb 39W
Lampholder / Socket	G5
Number of light sources	2
Lamp included	No
Installation length	92 cm
Installation width	18.8 cm
Installation depth	15.5 cm
Length	88.5 cm
Width	15.5 cm
Depth	15.5 cm
Net weight	4.973 kg
Gross weight	5.175 kg
Voltage	230 Volt
Max. wattage	78 Watt
Protection class	I
Material	steel / acrylic
Colour	black
Way of mounting	recessed ceiling mounting
Remark 1	Suitable for hollow core slabs with a thickness of up to 20 mm
Remark 2	Measurements installation frame (L / W / H): 92 / 24,5 / 7 cm
Remark 3	Including an incorporated electronic ballast
Remark 4	Energy labels in your language are available in the Service Area sub point Download
remark5	Suitable for all modules except the Aixlight Pro QRB and LED Disk modules
Energy class ballast	A2
Suitable for lamps from EEC	A

Suitable for lamps up to EEC	A+
Light distribution type 1	direct
Light distribution type 3	axisymmetric

The rectangular recessed fitting AIXLIGHT PRO T5 FRAMELESS is the start of a professional, modular system for cavity ceilings with a maximum material thickness of 20mm. Designed for the use of two T5 fluorescent tubes with an output of 39W each, AIXLIGHT PRO T5 FRAMELESS is covered by a satined acrylic shade. Thanks to the incorporated electronic ballast, the electrical connection is made directly via 230V mains supply. This luminaire is compatible with bulbs of the energy classes: A - A+