




## Die Lampen können in der Leuchte nicht ausgetauscht werden.



## **SUPROS 78**

ceiling light, LED, 3000K, round, black, 60° lens

Article number	116330
Product family	Supros Mini 750
Feed-in capability	No
Lamp included	Yes
Tilt range	60 Degree
Rotation range	350 Degree
Height	15.8 cm
Diameter	7.8 cm
Net weight	0.613 kg
Gross weight	0.678 kg
Voltage	220-240 ~50/60 . 250 Volts
Protection class	I
Beam angle	60 Degree
_ ca ag.c	00 = 0g. 00
Material	Aluminium
Material	Aluminium
Material Colour	Aluminium black
Material Colour Way of mounting	Aluminium black Surface ceiling mounting
Material Colour Way of mounting Average lifespan	Aluminium black Surface ceiling mounting 25000 Hours 3000 Kelvin
Material Colour Way of mounting Average lifespan Colour temperature	Aluminium black Surface ceiling mounting 25000 Hours 3000 Kelvin
Material Colour Way of mounting Average lifespan Colour temperature Colour rendering index	Aluminium black Surface ceiling mounting 25000 Hours 3000 Kelvin
Material Colour Way of mounting Average lifespan Colour temperature Colour rendering index Luminous flux	Aluminium black Surface ceiling mounting 25000 Hours 3000 Kelvin 80 700 Im
Material Colour Way of mounting Average lifespan Colour temperature Colour rendering index Luminous flux Energy efficiency class	Aluminium black Surface ceiling mounting 25000 Hours 3000 Kelvin 80 700 Im A++
Material Colour Way of mounting Average lifespan Colour temperature Colour rendering index Luminous flux Energy efficiency class fastCalcEnabled	Aluminium black Surface ceiling mounting 25000 Hours 3000 Kelvin 80 700 Im A++ Yes

The SUPROS luminaire impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.