





## **SUPROS**

pendant, LED, 4000K, round, white, 3000lm, 60° reflector, 28W

Article number	133111
Max. wattage	28 Watt
Light distribution type 1	Direct
Light distribution type 3	rotationally symmetric
Product family	Supros 3000
Feed-in capability	No
Lamp included	No
Height	18.5 cm
Diameter	12.7 cm
Pendant length	200 cm
Net weight	1.625 kg
Gross weight	1.738 kg
Voltage	220-240 ~50/60 . 750 Volts
Protection class	1
Protection class Beam angle	60 Degree
Beam angle	60 Degree
Beam angle Material	60 Degree Aluminium
Beam angle Material Colour	60 Degree Aluminium white
Beam angle Material Colour Way of mounting	60 Degree Aluminium white Ceiling mounted
Beam angle Material Colour Way of mounting Average lifespan	60 Degree Aluminium white Ceiling mounted 50000 Hours
Beam angle  Material  Colour  Way of mounting  Average lifespan  Colour temperature	60 Degree Aluminium white Ceiling mounted 50000 Hours 4000 Kelvin
Beam angle Material Colour Way of mounting Average lifespan Colour temperature Colour rendering index	60 Degree Aluminium white Ceiling mounted 50000 Hours 4000 Kelvin
Beam angle Material Colour Way of mounting Average lifespan Colour temperature Colour rendering index Luminous flux	60 Degree Aluminium white Ceiling mounted 50000 Hours 4000 Kelvin 80 2100 lm
Beam angle Material Colour Way of mounting Average lifespan Colour temperature Colour rendering index Luminous flux Energy efficiency class	60 Degree Aluminium white Ceiling mounted 50000 Hours 4000 Kelvin 80 2100 lm A++
Beam angle  Material  Colour  Way of mounting  Average lifespan  Colour temperature  Colour rendering index  Luminous flux  Energy efficiency class  fastCalcEnabled	60 Degree Aluminium white Ceiling mounted 50000 Hours 4000 Kelvin 80 2100 lm A++ Yes

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The widearea reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.