





SUPROS

pendant, LED, 3000K, round, black, 4000lm, 60° reflector, 33.5W

Article number	133140
Max. wattage	33.5 Watt
Light distribution type 1	Direct
Light distribution type 3	rotationally symmetric
Product family	Supros 4000
Feed-in capability	No
Lamp included	No
Height	18.5 cm
Diameter	12.7 cm
Pendant length	200 cm
Net weight	1.625 kg
Gross weight	1.739 kg
Voltage	220-240 ~50/60 . 950 Volts
Protection class	I
Beam angle	60 Degree
Material	Aluminium/glass
Colour	black
Way of mounting	Ceiling mounted
Average lifespan	50000 Hours
	30000 Hours
Colour temperature	3000 Hours
Colour temperature Colour rendering index	
·	3000 Kelvin
Colour rendering index	3000 Kelvin 80
Colour rendering index Luminous flux	3000 Kelvin 80 3150 lm
Colour rendering index Luminous flux Energy efficiency class	3000 Kelvin 80 3150 lm A++

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The widearea reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.