





SUPROS

pendant, LED, 4000K, round, black, 4000lm, 60° reflector, 33.5W

Max. wattage Light distribution type 1 Light distribution type 3 rotationally symmetric Product family Supros 4000 Feed-in capability No Lamp included No Height 18.5 cm Diameter 12.7 cm Pendant length 200 cm Net weight 1.62 kg Gross weight Voltage 220-240 ~50/60 . 950 Volts Protection class I Beam angle 60 Degree	Article number	133150
Light distribution type 3 rotationally symmetric Product family Supros 4000 Feed-in capability No Lamp included No Height 18.5 cm Diameter 12.7 cm Pendant length 200 cm Net weight 1.62 kg Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class I	Max. wattage	33.5 Watt
Product family Supros 4000 Feed-in capability No Lamp included No Height 18.5 cm Diameter 12.7 cm Pendant length 200 cm Net weight 1.62 kg Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class	Light distribution type 1	Direct
Feed-in capability Lamp included No Height 18.5 cm Diameter 12.7 cm Pendant length 200 cm Net weight 1.62 kg Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class	Light distribution type 3	rotationally symmetric
Lamp included No Height 18.5 cm Diameter 12.7 cm Pendant length 200 cm Net weight 1.62 kg Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class	Product family	Supros 4000
Height 18.5 cm Diameter 12.7 cm Pendant length 200 cm Net weight 1.62 kg Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class I	Feed-in capability	No
Diameter 12.7 cm Pendant length 200 cm Net weight 1.62 kg Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class I	Lamp included	No
Pendant length 200 cm Net weight 1.62 kg Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class I	Height	18.5 cm
Net weight 1.62 kg Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class I	Diameter	12.7 cm
Gross weight 1.75 kg Voltage 220-240 ~50/60 . 950 Volts Protection class I	Pendant length	200 cm
Voltage 220-240 ~50/60 . 950 Volts Protection class I	Net weight	1.62 kg
Protection class I	Gross weight	1.75 kg
	Voltage	220-240 ~50/60 . 950 Volts
Beam angle 60 Degree	Protection class	1
	Beam angle	60 Degree
Material Aluminium/glass	Material	Aluminium/glass
Colour black	Colour	black
Way of mounting Ceiling mounted	Way of mounting	Ceiling mounted
Average lifespan 50000 Hours	Average lifespan	50000 Hours
Colour temperature 4000 Kelvin	Colour temperature	4000 Kelvin
Colour rendering index 80	Colour rendering index	80
Luminous flux 3150 lm	Luminous flux	3150 lm
Energy efficiency class A++	Energy efficiency class	A++
fastCalcEnabled Yes	fastCalcEnabled	Yes
ranking 400	ranking	400
Catalogue page BIG WHITE 2017: 119	Catalogue page	BIG WHITE 2017: 119

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The widearea reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.