




160284


silvergrey, 70 LED, 3000K

Article number



Catalogue	BIG WHITE 2015, Page 423
Type of lamp	LED lamp
Lamp	SMD LED
Number of light sources	70
Lamp included	Yes
Installation diameter	18 cm
Installation depth	4.1 cm
Height	4.8 cm
Diameter	20 cm
Net weight	0.281 kg
Gross weight	1.831 kg
Voltage	230 Volt
Max. wattage	8.6 Watt
Protection class	II
Material	plastic






Ciross Weight	1.001 kg
Voltage	230 Volt
Max. wattage	8.6 Watt
Protection class	II
Material	plastic
Colour	silvergrey
Way of mounting	recessed ceiling mounting / recessed wall mounting
Remark 1	LED power supply incorporated
Remark 2	Only suitable for walls and ceilings with a maximum thickness of 20 mm
Remark 3	Energy labels in your language are available in the Service Area sub point Download
Average lifespan	20000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	500 lm
Suitable for	Δ

lamps from EEC

lamps up to EEC

Suitable for





Light distribution type 1	direct
Light distribution type 3	rotationally symmetric

The ultra-flat ECO LED wall and ceiling luminaire convinces by its low installation depth and is equipped with 70 warm white SMD LED for the round version and 100 warm white SMD LED for the square version. Thus, it ensures a high light output even at most difficult installations. Available in white and gray colour version, the electrical connection of both the round and the square version is made directly to 230V mains via the incorporated power supply. To achieve a glare-free light, the LEDs are installed behind a frosted cover. This luminaire contains built-in LED lamps. EEK: A - A++. The lamps cannot be changed in the luminaire.