


LEFA 1 DL downlight

round, white, 5W, 3000K, incl. driver and retaining




	L	7		
-	7	X	V	
H	4	$\langle \times \rangle$	$\langle \rangle$	
1	28	X	7	7
#	4	7	+	H
1	Į.	I	7	H
+00			Q	4
800	1	X	X	*
11		0.00	800	100



Article number	160571
Catalogue	BIG WHITE 2015, Page 403
Type of lamp	LED lamp
Lamp	planar LED 5W
Number of light sources	1
Lamp included	Yes
Installation diameter	7 cm
Installation depth	3.5 cm
Height	5 cm
Diameter	8 cm
Net weight	0.185 kg
Gross weight	0.496 kg
Voltage	230 Volt
Max. wattage	7.4 Watt
Protection class	II
Material	steel / plastic
Colour	white
Way of mounting	recessed ceiling mounting / recessed wall mounting
Remark 1	Only suitable for walls and ceilings with a maximum thickness of 25 mm
Remark 2	LED driver incorporated
Remark 3	Energy labels in your language are available in the Service Area sub point Download
Average lifespan	40000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	380 lm
Suitable for lamps from EEC	A
Suitable for lamps up to EEC	A++





Light distribution type 1	direct
Liedet elietuile.utieue	

Light distribution type 3 rotationally symmetric

The downlight LEFA 1 is characterized by its high performance warm white COB LED. Fitted into an ultra-slim, sophisticated design housing the installed LEDs are powered by the incorporated constant current driver. Thus, the electrical connection can be made directly to 230V mains supply. To extend the series, we offer a wall and ceiling lamp as well as a pendant version. This luminaire contains built-in LED lamps. EEK: A - A++. The lamps cannot be changed in the luminaire.