



## N-TIC ROUND

silvergrey, MR16, max. 35W, IP67

Article number	227450
Type of lamp	Conventional lamp
Lamp	MR16 12V max. 35W
Lampholder / Socket	G5,3
Number of light sources	1
Lamp included	No
Installation diameter	10.5 cm
Installation depth	11.2 cm
Tilt range	20 Degree
Diameter	11 cm
Net weight	0.626 kg
Gross weight	1.196 kg
Voltage	12 Volt
Max. wattage	35 Watt
Protection class	III
Material	aluminium
Colour	silvergrey
Way of mounting	recessed ground mounting
Remark 1	200 cm connection lead with mounting pot included
Remark 2	Weight capacity 500 kg
Remark 3	Through wiring is possible
Remark 4	Energy labels in your language are available in the Service Area sub point Download
Suitable for lamps from EEC	C
Suitable for lamps up to EEC	A+
Light distribution type 1	direct
Light distribution type 3	rotationally symmetric

Walkable, low-voltage recessed ground luminaire with round cover and partially satined glass. Rated IP67, it is suitable for outdoor use. To ensure accurate illumination, the lamp is adjustable. The electrical connection is made directly to 230V mains supply via a separately available transformer providing 12V alternating current. For simplified mounting, an installation housing is included offering through-wiring possibilities. We optionally offer a stainless steel or partially satined glass cover. This luminaire is compatible with bulbs of the energy classes: C - A+