





Article number

Type of lamp

Lampholder /

Lamp

square, stainl. steel, 316, Rx7s, max. 150W, IP67


Conventional lamp

HQI-TS / CDM-TD 150W

229304








Installation diameter	29 cm
Installation depth	39 cm
Length	27 cm
Width	27 cm
Net weight	9.363 kg
Gross weight	8.042 kg
Voltage	230 Volt
Max. wattage	150 Watt
Protection class	1
Material	aluminium / stainless steel 316
Colour	stainless steel
Way of mounting	recessed ground mounting
Remark 1	Conventional ballast incorporated. Mounting plot included
Remark 2	Weigth capacity 2 tons. Asymmetrical reflector
Remark 3	Through wiring is possible
Remark 4	Energy labels in your language are available in the Service Area sub point Download
Energy class ballast	A3
Suitable for lamps from EEC	A
Suitable for lamps up to EEC	A+
Light distribution type 1	direct
Light distribution type 3	asymmetric





The walkable recessed ground luminaire with a round stainless steel cover and partially satined glass is equipped with an adjustable Rx7s lampholder and a suitable ballast making it compatible with discharge lamps. Due to the integrated asymmetric reflector, a homogeneous and planar illumination is possible even with small distances to the illuminated surface. Rated IP67, DASAR is suitable for outdoor use. The electrical connection is made directly to 230V mains supply. For simplified mounting, a suitable installation housing is included. This luminaire is compatible with bulbs of the energy classes: A - A+