



OUT BEAM

outdoor wall light, LED, 3000K, beam up/flood down, silver-grey, IP44

| | |
|---------------------------|----------------------------|
| Article number | 229664 |
| Number of light sources | 4 |
| Max. wattage | 18 Watt |
| Lamp | PowerLED & 1 COB LED-Modul |
| Light distribution type 1 | direct-indirect |
| Feed-in capability | No |
| Lamp included | No |
| Width | 15 cm |
| Height | 15 cm |
| Depth | 15.8 cm |
| Net weight | 1.577 kg |
| Gross weight | 1.815 kg |
| Voltage | 120-277~50/60 . 500 Volts |
| Protection class | I |
| IP-rating | IP 44 |
| Beam angle | 80 Degree |
| Material | Aluminium/glass |
| Colour | silver |
| Way of mounting | Surface wall mounting |
| Average lifespan | 25000 Hours |
| Colour temperature | 3000 Kelvin |
| Colour rendering index | 80 |
| Luminous flux | 755 lm |
| Energy efficiency class | A++ |
| fastCalcEnabled | No |
| ranking | 400 |
| Catalogue page | BIG WHITE 2017: 637 |

The OUT BEAM series LED wall light, available in single-headed and double-headed versions, was designed especially as an architectural accent illumination. The LED light sources lie opposite each other and are covered by glass, they produce a narrow and a wide beam respectively and thus create the special up/down effect. Thanks to its IP44 protection class, the luminaire is suitable for outdoor use. The electrical connection of the luminaire is made directly to the 230V mains supply thanks to the built-in LED driver. The OUT BEAM series also includes wall lights for halogen lamps.

