




## EASYLITE SPOT ES111

stonegrey , max. 75W, IP44

|                              |   |
|------------------------------|---|
| Article number               | 230575  |
| Type of lamp                 | Conventional lamp   |
| Lamp                         | ES111 230V max. 75W   |
| Lampholder / Socket          | GU10  |
| Number of light sources      | 1   |
| Lamp included                | No  |
| Tilt range                   | 110 Degree  |
| Height                       | 23.5 cm   |
| Net weight                   | 1.542 kg  |
| Gross weight                 | 1.924 kg  |
| Voltage                      | 230 Volt  |
| Max. wattage                 | 75 Watt   |
| Protection class             | I   |
| Material                     | aluminium   |
| Colour                       | grey  |
| Way of mounting              | surface wall mounting / surface floor mounting / surface ceiling mounting           |
| Remark 1                     | Basis (Ø / H): 13 / 8 cm. Kopf (Ø / L): 15,5 / 23 cm                                |
| Remark 2                     | Maximum cable diameter 12 mm  |
| Remark 3                     | Energy labels in your language are available in the Service Area sub point Download |
| Suitable for lamps from EEC  | E   |
| Suitable for lamps up to EEC | A++   |
| Light distribution type 1    | direct  |

Aluminum luminaire of the EASYLITE SPOT series for floor, wall or ceiling mounting. Mounted to the junction box the lamp head is adjustable for individual illumination. Rated IP44 it is suitable for outdoor use. The electrical connection is made directly to 230V mains supply via the incorporated transformer. The EASYLITE SPOT series further includes versions for discharge, high-voltage halogen and energy-saving lamps. We additionally offer a suitable earth spike for simplified assembly. This luminaire is compatible with bulbs of the energy classes: E - A++

SLV Elektronik GmbH  
art.-no. 230575

 This luminaire is compatible with bulbs of the energy classes:

A++  
A+  
A  
B  
C  
D  
E

874 / 2012 