


N-TIC PRO MR16

round cover, stainless steel 316 brushed, max. 35W, IP67

| Article number | 230900 |
|------------------------------|---|
| Catalogue | BIG WHITE 2015, Page 670 |
| Type of lamp | Conventional lamp |
| Lamp | MR16 12V max. 35W |
| Lampholder / Socket | GU5,3 |
| Number of light sources | 1 |
| Lamp included | No |
| Installation diameter | 12.3 cm |
| Installation depth | 11.5 cm |
| Tilt range | 30 Degree |
| Rotation range | 90 Degree |
| Height | 11.5 cm |
| Diameter | 13.5 cm |
| Net weight | 1.795 kg |
| Gross weight | 2.416 kg |
| Voltage | 12 Volt |
| Max. wattage | 35 Watt |
| Protection class | III |
| Material | stainless steel 316 / glass |
| Colour | stainless steel brushed |
| Way of mounting | recessed ground mounting |
| Remark 1 | Weigth capacity 500 kg |
| Remark 2 | Additionally you will need a suitable transformer |
| Remark 3 | Mounting pot included |
| Remark 4 | Energy labels in your language are available in the Service Area sub point Download |
| Suitable for lamps from EEC | С |
| Suitable for lamps up to EEC | A+ |
| Light distribution type 1 | direct |
| Light distribution | rotationally symmetric |

type 3





Walkable, low-voltage recessed ground luminaire with round stainless steel cover and partially satined glass is equipped with a GU5.3 lampholder making it compatible with halogen or LED lamps. Rated IP67, it it suitable for outdoor use. The electrical connection is made directly to 230V mains supply via a separately available low-voltage transformer providing 12V alternating current. For simplified mounting, a installation housing is included. Alternatively to the ground it can also be used as recessed wall luminaire. This luminaire is compatible with bulbs of the energy classes: C - A+