



DASAR PROJECTOR

outdoor floodlight, LED, 3000K, IP67, anodised aluminium, 230V, 6W

Article number	233561
Max. wattage	5 Watt
Light distribution type	Direct
	1
Lamp included	No
Feed-in capability	No
Length	7.2 cm
Width	10 cm
Height	10.8 cm
Net weight	0.754 kg
Gross weight	0.832 kg
Voltage	220-240 ~50/60 . 400 Volts
Protection class	I
IP-rating	IP 67
Beam angle	40 Degree
Material	Aluminium/glass
Colour	anodised aluminium
Way of mounting	Floor mounted accessories / ceiling mounted accessories / wall mounted accessories
Average lifespan	25000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	300 lm
Energy efficiency class	A++
Type of plug	IP Schuko plug
fastCalcEnabled	No
ranking	400
Catalogue page	BIG WHITE 2017: 597

The surface-mounted DASAR PROJECTOR series lights are fitted with a 6W premium LED and available with a warm-white colour of light. The electrical connection is to a compatible 12V or 24V DC power supply. With IP68 protection class, the luminaire is suitable for outdoor use. The anodised aluminium DASAR PROJECTOR series includes a further stainless steel version, among other things. This luminaire has built-in LED lamps and can be used as a spike luminaire with an earth spike. EEL A - A++ The lamps in the luminaire cannot be replaced.