



IP FLEXLED ROLL 24V

25W, 5000K, 5m, 60 LED/m, IP55

Article number	552275
Catalogue	BIG WHITE 2015, Page 703
Type of lamp	LED lamp
Lamp	SMD LED
Number of light sources	300
Lamp included	Yes
Length	500 cm
Width	1.3 cm
Height	0.5 cm
Net weight	0.39 kg
Gross weight	0.505 kg
Voltage	24 Volt
Max. wattage	25 Watt
Beam angle	120 Degree
Material	plastic
Way of mounting	surface wall mounting / surface floor mounting / surface ceiling mounting
Remark 1	Strip embedded in plastic cover. Not extenable
Remark 2	Seperable every 10 cm. From a length of 500 cm a new feed-in must be made
Remark 3	Rear side equipped with adhesive tape
remark5	From a length of 500 cm a new feed-in must be made
Average lifespan	20000 Hours
Colour temperature	5000 Kelvin
Colour rendering index	80
Luminous flux	1550 lm
Energy class lamp	A
Weighted energy consumption	29 kWh/1000h



Plastic coated flexible 24V DC LED strip for outdoor usage. For simplified mounting the backside is covered with adhesive tape. The power input is given by a 24V PSU via a 50 cm connection lead. The strip is rated IP55 and thus also suitable for outdoor use. The product is rated EEC A. The weighted energy consumption is 29kWh/1000h.