


## FLEXSTRIP LED PROFESSIONAL

24V, LED strip, 2 m, 4000K





Article number	552584
Number of light sources	360
Voltage	24 Volts
Max. wattage	80 Watt
Protection class	III
Colour temperature	4000 Kelvin
Colour rendering index	80
Lamp	LED
Material	plastic
Lamp included	No
LED per meter	180 Meter
Feed-in capability	No
Length	200 cm
Length Width	200 cm 3.5 cm
-	
Width	3.5 cm
Width Height	3.5 cm 0.2 cm
Width Height Net weight	3.5 cm 0.2 cm 0.112 kg
Width Height Net weight Gross weight	3.5 cm 0.2 cm 0.112 kg 0.164 kg
Width Height Net weight Gross weight Colour	3.5 cm 0.2 cm 0.112 kg 0.164 kg white Surface wall / Surface floor / Surface ceiling
Width Height Net weight Gross weight Colour Way of mounting	3.5 cm 0.2 cm 0.112 kg 0.164 kg white Surface wall / Surface floor / Surface ceiling mounting
Width Height Net weight Gross weight Colour Way of mounting Luminous flux Energy efficiency	3.5 cm 0.2 cm 0.112 kg 0.164 kg white Surface wall / Surface floor / Surface ceiling mounting 8400 lm
Width Height Net weight Gross weight Colour Way of mounting Luminous flux Energy efficiency class	3.5 cm 0.2 cm 0.112 kg 0.164 kg white Surface wall / Surface floor / Surface ceiling mounting 8400 lm A+
Width Height Net weight Gross weight Colour Way of mounting Luminous flux Energy efficiency class fastCalcEnabled	3.5 cm 0.2 cm 0.112 kg 0.164 kg white Surface wall / Surface floor / Surface ceiling mounting 8400 lm A+

Flexible PROFI LED Strip, with exceptionally high luminous flux, for connection to 24V DC power adapter. To obtain constant light output over long lengths, the strips should be powered on both sides. The rear side is fitted with adhesive tape to make for simple installation. Available accessories for this strip, which is available with a number of different lengths and light colours, include: feed cables, clips, and direct connectors.