




CHART

EXTERIOR
FLOOR RECESSED



0.6

LED 5W | 220-240VAC | 50-60Hz
COB 3-step | incl. power supply
stainless steel | glass
aluminium powder coated

0.39kg IP67 0.3-16 38°


45 118

3000K | >80 CRI | 150lm

CODE
752163I4

OPTIONAL

CODE
recessed housing 90012201



0.9

LED 8W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

0.70kg IP67 0.3-16 38°


78 135

3000K | >80 CRI | 480lm

CODE
752264I4

OPTIONAL

CODE
recessed housing 90012202



1.2

LED 12W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

1.05kg IP67 0.3-16 38°


110 175

3000K | >80 CRI | 750lm

CODE
752364I4

OPTIONAL

CODE
recessed housing 90012203



1.6

LED 15W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

1.05kg IP67 0.3-16 38°

150 185

3000K | >80 CRI | 950lm

CODE
752464I4

OPTIONAL

CODE
recessed housing 90012204