




GO-ON  
CEILING SURFACE



1.0 LED111

LED 10W | 220-240VAC | 50-60Hz  
AC-COB 3-step | phase-cut dim  
aluminium powder coated


1.70kg IP20 0.3m P A 38°

45°/45° 45°/45°

| CODE    |  |
|---------|--|
| 116168W |  |
| 116168S |  |

Light Colour Selection

|       | LUMEN | CRI | CODE |
|-------|-------|-----|------|
| 2700K | 710   | >80 | 2    |
| 3000K | 730   | >80 | 4    |



2.0 LED111

2xLED 10W | 220-240VAC | 50-60Hz  
AC-COB 3-step | phase-cut dim  
aluminium powder coated


2.80kg IP20 0.3m P A 38°

45°/45° 45°/45°

| CODE    |  |
|---------|--|
| 116268W |  |
| 116268S |  |

Light Colour Selection

|       | LUMEN | CRI | CODE |
|-------|-------|-----|------|
| 2700K | 2x710 | >80 | 2    |
| 3000K | 2x730 | >80 | 4    |



3.0 LED111

3xLED 10W | 220-240VAC | 50-60Hz  
AC-COB 3-step | phase-cut dim  
aluminium powder coated

4.20kg IP20 0.3m P A 38°

45°/45° 45°/45°

| CODE    |  |
|---------|--|
| 116368W |  |
| 116368S |  |

Light Colour Selection

|       | LUMEN | CRI | CODE |
|-------|-------|-----|------|
| 2700K | 3x710 | >80 | 2    |
| 3000K | 3x730 | >80 | 4    |