



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.45kg IP20 3-0.3-1 36°

45/45° 10° 145 4-25

| | CODE |
|--|---------|
| | 117161W |
| | 117161S |
| | 117161B |

Light Colour Selection

| | LUMEN CRI | CODE |
|------------|---------------|------|
| 2700K | 420-590 >90 | 3 |
| 3000K | 470-640 >90 | 5 |
| 1800-2850K | 370-510 >90 | 9 |

ALWAYS USE

power supply

| | CODE |
|-----------------|----------|
| 350mA 10W | 90213402 |
| 500mA 10W | 90214403 |
| 500mA 15W dim | 90224501 |

more power supplies on page 468

1.0 PAR16

PAR16 max.50W | GU10
220-240VAC | 50-60Hz
aluminium powder coated

0.41kg IP20 3-0.9-1

45/45° 13° 145 4-25

| | CODE |
|--|----------|
| | 117120W0 |
| | 117120S0 |
| | 117120B0 |

OPTIONAL

PAR16 LED GU10 6W
phase-cut dim

| | CODE |
|------------|----------|
| 2700K | 901228W2 |
| 3000K | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 471

HIDE
CEILING RECESSED

ALWAYS USE

recessed housing + plaster kit

one lamp | 111x111x117mm

115x115 145 4-25

| | CODE |
|--|----------|
| | 90012009 |
| | 90012017 |

two lamps | 208x111x117mm

212x115 145 4-25

| | CODE |
|--|----------|
| | 90012010 |
| | 90012018 |

three lamps | 302x111x117mm

306x115 145 4-25

| | CODE |
|--|----------|
| | 90012011 |
| | 90012019 |

four lamps | 398x111x117mm

402x115 145 4-25

| | CODE |
|--|----------|
| | 90012012 |
| | 90012020 |

more information on page 479