

1.0 LED HV

LED 7W | 220-240VAC
PCB 3-step | incl. PS | phase-cut dim
aluminium | stainless steel
opal cover | polyamide| PMMA

0.18kg IP44 0,3-1 P

76 50 2-25


3000K | >90 CRI | 350lm

	CODE
	114388W5
	114388M5
	114388B5

OPTIONAL

dimmer	
	CODE
for switch	90019017
for din rail	90019018
more specs on page 540	

	CODE
recessed housing	90012026
plasterkit	90017101



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium | stainless steel
opal glass | polyamide

0.19kg IP44 0,3-1 G

80 100 2-25

	CODE
	114381W
	114381M
	114381B

Light Colour Selection

	LUMEN CRI	CODE
2700K	360-510 >90	3
3000K	400-540 >90	5
1800-2850K	270-370 >95	9


ALWAYS USE

power supply	
	CODE
350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501

more power supplies on page 538

OPTIONAL

	CODE
recessed housing	90012026
plasterkit	90017101



1.0 PAR16

PAR16 max.10W | GU10
100-240VAC | 50-60Hz
aluminium | stainless steel
opal glass | polyamide

0.24kg IP44 0,9-1 G


80 120 2-25

	CODE
	114120W0
	114120M0
	114120B0

OPTIONAL

PAR16 LED GU10 7W	
phase-cut dim	
	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9
more lamps and specs on page 541	

	CODE
recessed housing	90012026
plasterkit	90017101



1.0 MR16

QR-CBC51 max.10W | GU5.3
12V | excl. power supply
aluminium | stainless steel
opal glass | polyamide

0.28kg IP44 0,9-1 G

80 100 2-25

	CODE
	114110W0
	114110M0
	114110B0

ALWAYS USE

power supply	
	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904
more specs on page 540	

OPTIONAL

	CODE
recessed housing	90012026
plasterkit	90017101

LUNA ROUND

CEILING RECESSED