



1.0 LED HV

LED 7W | 220-240VAC
PCB 3-step | incl. PS | phase-cut dim
aluminium | stainless steel
opal cover | polyamide | PMMA

0.19kg IP44 0.3m P

72x72 50 2-25

3000K | >90 CRI | 350lm

	CODE
	114488W5
	114488M5
	114488B5

OPTIONAL

dimmer	
	CODE
for switch	90019017
for din rail	90019018
more specs on page 540	

	CODE
recessed housing	90012026
plasterkit	90017102

1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium | stainless steel
opal glass | polyamide

0.20kg IP44 0.3m G

76x76 100 2-25

	CODE
	114481W
	114481M
	114481B

Light Colour Selection

	LUMEN CRI	CODE
2700K	360-510 >90	3
3000K	400-540 >90	5
1800-2850K	270-370 >95	9

ALWAYS USE

power supply	
	CODE
350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501
more power supplies on page 538	

OPTIONAL

	CODE
recessed housing	90012026
plasterkit	90017102

1.0 PAR16

PAR16 max.10W | GU10
100-240VAC | 50-60Hz
aluminium | stainless steel
opal glass | polyamide

0.26kg IP44 0.9m G

76x76 120 2-25

	CODE
	114220W0
	114220M0
	114220B0

OPTIONAL

PAR16 LED GU10 7W phase-cut dim	
	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9
more lamps and specs on page 541	

	CODE
recessed housing	90012026
plasterkit	90017102

1.0 MR16

QR-CBC51 max.10W | GU5.3
12V | excl. power supply
aluminium | stainless steel
opal glass | polyamide

0.28kg IP44 0.9m G

76x76 100 2-25

	CODE
	114210W0
	114210M0
	114210B0

ALWAYS USE

power supply	
	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904
more specs on page 540	

OPTIONAL

	CODE
recessed housing	90012026
plasterkit	90017102