




PLUXO
CEILING SURFACE



3.0 LED

3xLED 8W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
aluminium powder coated


1.59kg IP20 36°

45°/45° 10°

	CODE
	142364W
	142364S
	142364B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	3x470	>90	3
3000K	3x470	>90	5
1800-2850K	3x410	>95	9



3.0 PAR16

3xPAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

1.23kg IP20 13°

45°/45° 13°


	CODE
	142320W0
	142320S0
	142320B0

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 541



4.0 LED

4xLED 8W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
aluminium powder coated


2.12kg IP20 36°

45°/45° 10°

	CODE
	142464W
	142464S
	142464B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	4x470	>90	3
3000K	4x470	>90	5
1800-2850K	4x410	>95	9



4.0 PAR16

4xPAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

1.64kg IP20 13°

45°/45° 13°

	CODE
	142420W0
	142420S0
	142420B0

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 541