




RAY  
WALL SURFACE



1.0 LED


LED 8W | 220-240VAC | 50-60Hz  
PCB 3-step | incl. PS | phase-cut dim  
aluminium powder coated brushed  
incl. flaps for adjustable beam angle

0.62kg IP20 3-10°

|  | CODE    |
|--|---------|
|  | 332168W |
|  | 332168L |
|  | 332168G |
|  | 332168Q |
|  | 332168P |
|  | 332168B |

Light Colour Selection

|            | LUMEN | CRI | CODE |
|------------|-------|-----|------|
| 2700K      | 400   | >80 | 2    |
| 3000K      | 440   | >80 | 4    |
| 1800-2850K | 400   | >80 | 9    |



1.0 QT14

QT14 max.75W | G9  
220-240VAC | 50-60Hz  
aluminium powder coated  
brushed

0.62kg IP20 3-10°

|  | CODE     |
|--|----------|
|  | 3221G0W0 |
|  | 3221G0L0 |
|  | 3221G0G0 |
|  | 3221G0Q0 |
|  | 3221G0P0 |
|  | 3221G0B0 |


OPTIONAL

QT14 LED 3W

|               | CODE     |
|---------------|----------|
| 3000K   300lm | 9019G704 |

flaps for adjustable beam angle

|  | CODE     |
|--|----------|
|  | 900401W0 |



2.0 LED


2xLED 4W | 220-240VAC | 50-60Hz  
PCB 3-step | incl. PS | phase-cut dim  
aluminium powder coated brushed  
incl. flaps for adjustable beam angle

0.69kg IP20 3-10°

|  | CODE    |
|--|---------|
|  | 332148W |
|  | 332148L |
|  | 332148G |
|  | 332148Q |
|  | 332148P |
|  | 332148B |

Light Colour Selection

|            | LUMEN | CRI | CODE |
|------------|-------|-----|------|
| 2700K      | 2x200 | >80 | 2    |
| 3000K      | 2x220 | >80 | 4    |
| 1800-2850K | 2x200 | >80 | 9    |



3.0 LED

2xLED 4W | 220-240VAC | 50-60Hz  
PCB 3-step | incl. PS | phase-cut dim  
aluminium powder coated brushed  
incl. flaps for adjustable beam angle

0.85kg IP20 3-10°

|  | CODE    |
|--|---------|
|  | 332248W |
|  | 332248L |
|  | 332248G |
|  | 332248Q |
|  | 332248P |
|  | 332248B |

Light Colour Selection

|            | LUMEN | CRI | CODE |
|------------|-------|-----|------|
| 2700K      | 2x200 | >80 | 2    |
| 3000K      | 2x220 | >80 | 4    |
| 1800-2850K | 2x200 | >80 | 9    |