



1.0 LED

LED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.16 kg | IP44 | 0.3-1° | 6 | 38°

76 | 60 | 4-30

|  | CODE     |
|--|----------|
|  | 154161W_ |
|  | 154161B_ |

Light Colour Selection

|            | LUMEN   CRI   | CODE |
|------------|---------------|------|
| 2700K      | 420-590   >90 | 3    |
| 3000K      | 470-640   >90 | 5    |
| 1800-2850K | 320-440   >95 | 9    |

ALWAYS USE

power supply

|                 | CODE     |
|-----------------|----------|
| 350mA   10W     | 90213402 |
| 500mA   10W     | 90214403 |
| 500mA   15W dim | 90224501 |

more power supplies on page 538

1.0 MR16

QR-CBC51 max. 35W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.10 kg | IP44 | 0.9-1° | 6

76 | 70 | 4-30


|  | CODE     |
|--|----------|
|  | 154110W0 |
|  | 154110B0 |

ALWAYS USE

power supply

|               | CODE     |
|---------------|----------|
| 12V   10W dim | 90221401 |
| 12V   25W dim | 90221701 |
| 12V   70W dim | 90221904 |

more specs on page 540



1.0 PAR16

PAR16 max. 35W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.14 kg | IP44 | 0.9-1° | 6

76 | 95 | 4-30

|  | CODE     |
|--|----------|
|  | 154120W0 |
|  | 154120B0 |

OPTIONAL

PAR16 LED GU10 7W  
phase-cut dim

|            | CODE     |
|------------|----------|
| 2700K      | 901228W2 |
| 3000K      | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 541