




RONY
CEILING RECESSED



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.34kg IP20 35°/35° 355° 90 4-40

102 35°/35° 355° 90 4-40

	CODE
110161W_	
110161S_	
110161B_	

blade springs

	CODE
110161W_C	

Light Colour Selection

	LUMEN CRI	CODE
2700K	420-590 >90	3
3000K	470-640 >90	5
1800-2850K	320-440 >95	9

ALWAYS USE

power supply

	CODE
350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501

more power supplies on page 538

1.0 MR16

QR-CBC51 max.35W | GU5.3
12V | excl. power supply
aluminium powder coated

0.28kg IP20 35°/35° 355° 75 4-40

102 35°/35° 355° 75 4-40

	CODE
110110W0	
110110S0	
110110B0	

blade springs

	CODE
110110W0C	

ALWAYS USE

power supply

	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 540

1.0 PAR16

PAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.32kg IP20 35°/35° 355° 100 4-40

102 35°/35° 355° 100 4-40

	CODE
110120W0	
110120S0	
110120B0	

blade springs

	CODE
110120W0C	

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 541