

SIRRO

26-11-2015

1.0 LED - ceiling surfaced

LED 10W | 220-240VAC | 50-60Hz | COB 3-step | incl. PS | phase-cut dim

CE IP20 960°C 0,3m 36° 35°/35° 355°

white texture
white texture + black
aluminium brushed + black

139164W_
139164E_
139164F_

LIGHT COLOUR

2200K | >80CRI | 465lm 1
2700K | >90CRI | 590lm 3
3000K | >90CRI | 640lm 5

1.0 PAR16 - ceiling surfaced

PAR16 max. 35W | GU10 | 220-240VAC | 50-60Hz

CE IP20 960°C 0,9m 35°/35° 355°

white texture

139120W0

OPTIONAL

for PAR16 lamps see our catalogue

1.0 LED - suspended

LED 10W | 220-240VAC | 50-60Hz | COB 3-step | incl. PS | phase-cut dim

CE IP20 960°C 0,3m 36° 35°/35° 355°

white texture
white texture + black
aluminium brushed + black

139564W_
139564E_
139564F_

LIGHT COLOUR

2200K | >80CRI | 465lm 1
2700K | >90CRI | 590lm 3
3000K | >90CRI | 640lm 5

1.0 PAR16 - suspended

PAR16 max. 35W | GU10 | 220-240VAC | 50-60Hz

CE IP20 960°C 0,9m 35°/35° 355°

white texture

139520W0


OPTIONAL

for PAR16 lamps see our catalogue



CEILING SURFACED

SUSPENDED


2




3



4





* wired spring version from inset also compatible



5




6




DIMENSIONS


CEILING SURFACED



SUSPENDED



BASE PLATE DIMENSIONS




POWER CABLE ENTERS HERE

MOUNTING INSTRUCTION

POWER CONNECTION

- 1 PARALLEL CONNECTION - for LED and PAR16



- 2 Mount the ceiling base on the ceiling
- 3 Attach the SIRRO to the ceiling base (in case of surfaced version)
- 4 Insert the outer part of the inset module into the SIRRO
- 5 Insert the lamp into the inner part of the inset module
- 6 Click the inner part of the inset module into the outer part



WEVER & DUCRÉ
LIGHTING

www.weverducre.com

INSTALLATION
INSTRUCTIONS