



**Light source**  
**Work equipment**  
**Connected load**  
**Power consumption**  
**Standby**  
**Power factor**  
**Luminous flux**  
**Light type/-color**  
**Colour temperatur**  
**Color rendering index**  
**Light distribution**  
**Direct ratio**  
**Beam angle**  
**Chromaticity tolerance LED**  
**Glare control**  
**Luminance (L65)**  
**System of protection**  
**Technology**  
**Operation**  
**Housing**  
**Light source cover**  
**Dimming Range**  
**Weight (net)**  
**Mains lead**  
**Fastening**  
**Configuration**  
**Dimension**  
**Life expectancy LED**  
**Special features**

LED  
Adjustable electronic ballast, digital DALI  
220 - 240 V; 50 Hz; 60 Hz  
ca. 10 W  
ca. 0,2 W  
env. 0,970  
approx. 1.000 lm  
Warm white  
approx. 3.000 K  
CRI  $\geq$  80  
Direct  
approx. 100 %  
86°  
< 3 SDCM  
Conical prismatic screen  
 $\leq$  3.000 cd/m<sup>2</sup>  
IP 40  
Continuously dimmable  
External  
Sectional aluminium; Silver  
Acrylic (PMMA); Clear  
1-100%  
ca. 3,1 kg  
ca. 2 m; With free stranded wires  
Steel cable 0.3 - 0.7 m  
Single Luminaire  
L=854mm  
L90B50 50.000h  
Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch