


CEE 7/VII

D43 ↓ 13.0% ↑ 87.0%



#### Light source

#### Work equipment

#### Connected load

#### Power consumption

#### Power factor

#### Luminous flux

#### Luminous efficiency

#### Light type/-color

#### Colour temperatur

#### Color rendering index

#### Light distribution

#### Direct ratio

#### Chromaticity tolerance LED

#### Glare control

#### Luminance (L65)

#### Unified glare rating (4H 8H)

#### System of protection

#### Class of protection

#### Technology

#### Operation

#### Housing

#### Light source cover

#### Arm

#### Luminaire base

#### Weight (net)

#### Mains lead

#### Fastening

#### Life expectancy LED

#### Special features

LED

Electronic ballast DALI

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 210 W; 214 W

env. 0,966

approx. 30.000 lm

approx. 142 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect

approx. 13 %

< 3 SDCM

Conical prismatic screen

≤ 2.700 cd/m<sup>2</sup>

≤ 16

IP 20

I

Presence and daylight sensor control (PIR); DALI;

Touch DIM

Wireless switch

Aluminium/plastic; Powder coatet; White

Acrylic (PMMA)

Steel tube; Powder-coated; Tubular section  
upright; White

C-form flat

ca. 26 kg

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

L80B50 60.000h

Asymmetric radiation; Flicker-free; App control;  
Direct and indirect lighting component with edge  
light and light guide technology for a  
homogeneous light exit; PIR movement and  
daylight sensor; TALK Bluetooth; Magnetic control  
panel, freely positionable