



Light source
Work equipment
Connected load
Power consumption
Standby
Power factor
Luminous flux
Light type/-color
Colour temperatur
Color rendering index
Light distribution
Direct ratio
Beam angle
Chromaticity tolerance LED
Glare control
Luminance (L65)
System of protection
Technology
Operation
Housing
Light source cover
Dimming Range
Weight (net)
Fastening
Configuration
Life expectancy LED
Special features

LED
Adjustable electronic ballast, digital DALI
220 - 240 V; 50 Hz; 60 Hz
ca. 13 W
ca. 0,2 W
env. 0,970
approx. 1.300 lm
Warm white
approx. 3.000 K
CRI \geq 80
Direct
approx. 100 %
86°
< 3 SDCM
Conical prismatic screen
 \leq 3.000 cd/m²
IP 40
Continuously dimmable
External
Sectional aluminium; White
Acrylic (PMMA); Clear
1-100%
ca. 4,3 kg
Steel cable 0.3 - 0.7 m
Middle luminaire
L90B50 50.000h
Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; 90° rerouting on the right side; Continuous light without dark zone; TouchDIM - dimming via standard switch