



Light source
Work equipment
Connected load
Power consumption
Standby
Power factor
Luminous flux
Light type/-color
Colour temperatur
Color rendering index
Light distribution
Direct ratio
Chromaticity tolerance LED
Glare control
Luminance (L65)
Unified glare rating (4H 8H)
System of protection
Technology
Operation
Housing
Light source cover
Dimming Range
Weight (net)
Fastening
Configuration
Life expectancy LED
Special features

LED
Adjustable electronic ballast, digital DALI
220 - 240 V; 50 Hz; 60 Hz
ca. 23 W
ca. 0,2 W
env. 0,970
approx. 3.000 lm
Warm white
approx. 3.000 K
CRI ≥ 80
Direct/indirect
approx. 40 %
< 3 SDCM
Conical prismatic screen
≤ 2.700 cd/m²
≤ 16
IP 40
Continuously dimmable
External
Sectional aluminium; Silver
Acrylic (PMMA); Clear
1-100%
ca. 4,5 kg
Steel cable 0.3 - 0.7 m
Middle luminaire
L90B50 50.000h
Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; 90° rerouting on the left side; Continuous light without dark z; TouchDIM - dimming via standard switch