

825923

Product Sheet

ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico

v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)

www.aresill.net - flos.outdoor@flos.com

Alice


Rectangular luminaire for installation in the wall - recessed. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: sandblasted. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN 60598-1 standards Class of insulation: I, LED module: I, III Installation: wiring through two M16 plastic cable glands (4,5<ø<10mm) placed on the back side of the fitting. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland. Installation requires a dedicated box to be ordered separately.

IP65   CE

Available Colors for this Version



Alice / All Light



Warnings

Wall Recessed



Recessed wall fitting



The fitting is equipped with 2 cable input.



Remote device required



Protection against impact.
IK 08 - 05,00 joule

Light Flux, Placement



Product Code Details

825923

Light Source



TC-DEL 18W G24q-2
Electronic ballast



Accessories



Code: 77
Box for installation
236 x 136 H 103 mm