Product Sheet




ARES s.r.l - Socio Unico

v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

Anna

Outdoor / Indoor round luminaire for installation on ceiling or wall surface-mounted. Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws. The luminaire is coated with polyester powders in single or double colour. Protection rating: IP65 In compliance with EN 60598-1 standards Class of Insulation: I Installation: the luminaire is equipped with two IP65 cable holders for rubber cables 5<Ø<10mm (Anna Ø210 and Ø310) or cables 6<Ø<13mm (Anna Ø410) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

Anna310 Mid-Power LED



Product Code Details

533011

Light Source




NATURAL WHITE 4000K MID-POWER LEDs 14,1W/220÷240V Total power 18W LED Im 2153 ÷ OUTPUT Im 1258 CRI>80

Integral electronic power supply Dimmable on request



IP65 ♥ ⊕ C€

Available Colors for this Version



Warnings

Decorative





The fitting is equipped with 2 cable input.



Wall fitting

Wall/Ceiling



Ceiling fitting



Protection against impact IK 08 - 05,00 joule

Protection against impact. IK 08 - 05,00 joule



The fitting is equipped with 2 cable input.



Wall fitting

Light Flux, Placement









Code: 237 SPD: (Surge Protection Device) 275Vac Maximum discharge current 10KA (8/20µs) Maximum operating current 5A Suitable for series connection - IP66