

10321135

Product Sheet

ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico

v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)

www.aresill.net - flos.outdoor@flos.com

Ara


Square luminaire for installation in the ceiling- recessed. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: transparent or sandblasted fixed to the frame through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN 60598-1 standards Class of insulation: mains: I, low voltage: III, LED module: I,II Installation: Ara GZ10/GU5,3 125x125: pre-wired with approx. 250mm cable. Ara LED 125x125: prewired with approx. 1000mm cable. Ara fluorescent 250x250: prewired with approx. 1000mm cable. Ara metal halide 250x250: equipped with one M16 plastic cable gland. Ara LED 250x250: equipped with two M16 plastic cable glands. The luminaire is ready for installation on false-ceiling (up to 30mm thick surfaces). Installation on solid ceiling requires a dedicated metal box to be ordered separately. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland / connector. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire

IP65  

Available Colors for this Version



Ara / 250x250 mm - All Light - Sandblasted Glass



Warnings

Ceiling Recessed



Recessed ceiling fitting



Protection against impact.
IK 06 - 1,00 joule



Ara LED 125x125mm
Ara fluorescent 250x250mm
Pre-wired with approx 1m of cable.

Light Flux, Placement



Product Code Details

10321135

Light Source




TC-TEL 42W Gx24 q-4

Electronic ballast



Accessories



Code: 108
Metal box for installing in concrete ceiling
450 x 300 x H 150 mm



Code: 215
3/4 way terminal block 3 poles IP68
(Ø 5,5÷12 mm cable)



Code: 236
2 way terminal block 3 poles IP68
(Ø 5,5÷12 mm cable)

