

# 1033323

Product Sheet

**ares**  
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico  
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)  
www.aresill.net - flos.outdoor@flos.com

## Ara



Square luminaire for installation in the ceiling- recessed. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: transparent or sandblasted fixed to the frame through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN 60598-1 standards Class of insulation: mains: I, low voltage: III, LED module: I,II Installation: Ara GZ10/GU5,3 125x125: pre-wired with approx. 250mm cable. Ara LED 125x125: prewired with approx. 1000mm cable. Ara fluorescent 250x250: prewired with approx. 1000mm cable. Ara metal halide 250x250: equipped with one M16 plastic cable gland. Ara LED 250x250: equipped with two M16 plastic cable glands. The luminaire is ready for installation on false-ceiling (up to 30mm thick surfaces). Installation on solid ceiling requires a dedicated metal box to be ordered separately. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland / connector. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire

IP65   

### Available Colors for this Version



### Ara / 125x125 mm - Transparent Glass - Adjustable Optic



### Warnings

#### Ceiling Recessed



Recessed ceiling fitting



Ara LED 125x125mm  
Ara fluorescent 250x250mm  
Pre-wired with approx 1m of cable.



Ara GZ10/GU5,3 125x125mm  
Pre-wired with approx 250mm of cable.



Protection against impact.  
IK 06 - 1,00 joule

### Light Flux, Placement



### Product Code Details

# 1033323

Light Source



QR CBC 51 50W/12V GU5,3  
Remote transformer to be ordered

**B**



Code: 107  
Metal box for installing in concrete ceiling  
250 x 200 x H 120 mm



Code: 16  
Transformer 50W  
230V/12V 50Hz  
IP 66



Code: 17  
Transformer 200W  
230V/12V 50Hz  
IP 66



Code: 18  
Transformer 300W  
230V/12V 50Hz  
IP 66



Code: 215  
3/4 way terminal block 3 poles IP68  
(Ø 5,5÷12 mm cable)



Code: 236  
2 way terminal block 3 poles IP68  
(Ø 5,5÷12 mm cable)

