

# 115147116

Product Sheet

**ares**  
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico  
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)  
www.aresill.net - flos.outdoor@flos.com

## Camilla


Rectangular luminaire for installation in the wall - recessed. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: sandblasted with silkscreen border, fixed to the aluminium structure through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN 60598-1 standards Class of insulation: mains: I; LED module: I, III; RGB: III Installation: Electrical components housed into the removable back side. Wiring through two M16 cable glands for (4,5 10mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland. Installation requires a dedicated box to be ordered separately.

IP65   CE

### Available Colors for this Version



### Camilla Mid-Power LED / L 300 mm - Diffused light



### Warnings

#### Wall Recessed



Recessed wall fitting



Remote device required for 24V version



The fitting is equipped with 2 cable input.



Protection against impact. IK 08 - 05,00 joule

### Light Flux, Placement



### Product Code Details

# 115147116

Light Source



WARM WHITE 3000K MID-POWER LEDs 6W/100÷240V  
Total power 10W  
lm LED 795 ÷ lm OUTPUT 160  
CRI >80  
Integral electronic power supply




## Accessories

---



Code: 124  
Box for installation  
325 x 110 x H 95 mm



Code: 237  
SPD: (Surge Protection Device) 275Vac  
Maximum discharge current 10KA (8/20µs)  
Maximum operating current 5A  
Suitable for series connection - IP66