115147117

Product Sheet

Camilla


Rectangular luminaire for installation in the wall - recessed. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: sandblasted with silkscreen border, fixed to the aluminium structure through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN 60598-1 standards Class of insulation: removable back side. Wiring through two M16 cable glands for (4,5 10mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland. Installation requires a dedicated box to be ordered separately.




ARES s.r.I - Socio Unico v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy) www.aresill.net - flos.outdoor@flos.com

IP65 🗑 ⊕ � € €

Available Colors for this Version



Warnings



In age not folmage not found http://www.ahttp://www.aptesill_nat/ixag/prod_lamp_placement/.png

Product Code Details

Light Source



Image not found http://www.aresill.net/img/prod_lightsources/.jpg

Image not found http://www.aresill.net/img/prod_energylabels/_.png

This product has no accessories