

# 9418612

Product Sheet


**ares**  
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico  
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)  
www.aresill.net - flos.outdoor@flos.com

## Cielo


Linear luminaire for installation in ground or ceiling - recessed. Configuration: extruded aluminium body and die-cast double closing end on each side. Glass diffuser: 8mm thick transparent or sandblasted with silkscreen border, fixed to the aluminium body through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP67 In compliance with EN 60598-1 standards Class of insulation: fluorescent lamp: II; LED module: I; RGB module: II Installation: the electrical components are installed on a removable frame. Wiring through two plastic M20 cable glands (6<math>\phi</math><math><12\text{mm}</math> cables) placed on one of the two closing ends where a plastic box allows connection to the removable electric module. RGB version: the luminaire is equipped with two pieces of cable for an easy-to-make connection. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland. Installation requires a dedicated box to be ordered separately. It is important to provide a >200mm gravel layer or a drain system (for concrete surfaces) to ensure good drainage and to avoid water stagnation. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

### Cielo Power LED / L 645 mm - Transparent Glass - Adjustable Optic - Narrow Beam 10°



IP67

### Available Colors for this Version



6. grey

### Warnings

#### Ground Recessed



Recessed ground fitting



The fitting is equipped with 2 cable input.



Protection against impact. IK 09 - 10,00 joule



Check that diffuser's temperature 'T max °C' (tested at 25°C) complies with your local regulation. Glass surface temperature



Do not install in hollow areas



Static load: 1500Kg walk over



Installation requires a 20 cm water drainage layer (gravel)

#### Ceiling Recessed



The fitting is equipped with 2 cable input.



Ceiling recessed installation. (for L 645 and L 1245 version only)



Protection against impact. IK 09 - 10,00 joule

### Product Code Details

# 9418612

Light Source



NATURAL WHITE 4000K POWER LEDs 13,2W/220÷240V  
Total power 16W  
LED lm 1560 ÷ OUTPUT lm 1423  
CRI >80  
Integral electronic power supply



### Light Flux, Placement



## Accessories

---



Code: 71  
Box for installation  
835 x 95 H 95 mm



Code: 81  
Frame for recessed installation on ceiling  
670 x 100 x H8 mm



Code: 237  
SPD: (Surge Protection Device) 275Vac  
Maximum discharge current 10KA (8/20 $\mu$ s)  
Maximum operating current 5A  
Suitable for series connection - IP66