

# 542006

Product Sheet

**ares**  
THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico  
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)  
www.aresill.net - flos.outdoor@flos.com

## Eclipse


Slim round luminaire for installation on wall - surface mounted. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content), stainless steel bracket and transparent polycarbonate emitting unit. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN60598-1 standards Class of insulation: II; 24V version: III Installation: the luminaire is equipped with a piece of neoprene cable (approx. 200mm) for an easy-to-make connection. Direct screwing on surface through the stainless steel bracket. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

IP65   

### Available Colors for this Version




### Eclipse Mid-Power LED



### Warnings

#### Wall



### Product Code Details

# 542006

Light Source



WARM WHITE 3000K MID-POWER LEDs 6W/24Vdc  
Total power 7,5W  
LED lm 795 ÷ OUTPUT lm 416  
CRI >80  
Remote electronic power supply to be ordered  
Dimmable on request, acc.: 144,176



### Light Flux, Placement



## Accessories

---



Code: 87  
Supported n. of lamps: 1  
Power supply  
10W/110÷240V - 24Vdc  
IP20 CLASS II SELV.



Code: 175  
Supported n. of lamps: 1  
Power supply  
10W/110÷240V - 24Vdc  
IP67 CLASS II SELV.



Code: 144  
Supported n. of lamps: 2  
Power supply  
17W/110÷240V - 24Vdc  
(15W@110V) IP20 CLASS II SELV.



Code: 176  
Supported n. of lamps: 2  
Power supply  
17W/110÷240V - 24Vdc  
(15W@110V) IP67 CLASS II SELV.



Code: 147  
Supported n. of lamps: 2  
Power supply  
20W/220÷240V - 24Vdc  
IP67 CLASS II SELV.



Code: 155  
Supported n. of lamps: 6  
Power supply  
50W/120÷240V - 24Vdc  
IP67 CLASS II SELV.



Code: 110  
Supported n. of lamps: 9  
Power supply  
70W/220÷240V - 24Vdc  
IP67 CLASS II SELV EQ.



Code: 156  
Supported n. of lamps: 12  
Power supply  
100W /120÷240V - 24Vdc  
IP67 CLASS II SELV.